



\*ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.  
 \*ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.  
 \*TANKS ORDERED WITH FOAM INSULATION WILL HAVE AN INCREASED DIAMETER OF 4-6 INCHES.  
 \*Consult Snyder's Guidelines for Use and Installation prior to delivery.  
 Available on-line at

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE.  
 ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A ± 3% TOLERANCE.

|                         |  |          |   |              |
|-------------------------|--|----------|---|--------------|
| DO NOT SCALE            |  | DRAWN BY | TITLE                                   | REVISION     |
| STATUS: <b>Released</b> |  | ETS      | <b>ASM TK 1550CP X 64</b>               | <b>A</b>     |
| HPTC-54900DC-SI         |  |          | PART NO. <b>5490000N &amp; 5460000N</b> | SHEET 1 OF 1 |
|                         |  |          | ENG. ID. <b>A003550</b>                 |              |

