



*ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.
 *ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.
 *TANKS ORDERED WITH FOAM INSULATION WILL HAVE AN INCREASED DIAMETER OF 4-6 INCHES.
 *Consult Snyder's Guidelines for Use and Installation prior to delivery.
 Available on-line at

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE.
 ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A ± 3% TOLERANCE.

| 2 | 1 | 34700088 | ASM CAP 10IN PE W/TIE |
|-----------------------|------|--------------|-------------------------|
| 1 | 1 | 8010000N__02 | ASM TK 110VCT X 33 NOMW |
| ITEM NO. | QTY. | PART NUMBER | DESCRIPTION |
| DO NOT SCALE | | DRAWN BY | TITLE: |
| Released | | SB | ASM TK 110VDT X 33 |
| HPTC-80100-SI | | | REVISION: A |
| PART NO. 8010000N__01 | | | ENG. ID. D011207 |
| | | | SHEET 1 OF 1 |