



FITTING FLAT ON THIS SIDE WILL NOT ACCEPT A FITTING WITH A SIPHON TUBE

FITTINGS ON THIS FLAT MUST BE CONNECTED WITH A FLEXIBLE CONNECTOR CAPABLE OF A MIN. 10° DOWNWARD ANGLE (NOTE REQUIRED ON DWG)

***ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.**
***ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.**
***TANKS ORDERED WITH FOAM INSULATION WILL HAVE AN INCREASED DIAMETER OF 4-6 INCHES.**
***Consult Snyder's Guidelines for Use and Installation prior to delivery.**
 Available on-line at

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE.
 ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A ± 3% TOLERANCE.

DO NOT SCALE		DRAWN BY	TITLE	REVISION
Released		BH	ASM TK 2600HLT X 82	A
HPTC-84700LC-SI			ENG. ID.	SHEET
			D011431	1 OF 1

